

Specification text - EMU Bottom intake pump - Material Design „A“

Item	Description	Unit price	Quantity	Total price
1	<p>Waterworks design, material design "C/D"</p> <p>Especially designed for the operation with low water levels. For the application in polders, tanks, rivers, lakes and as replacement for shaft pumps.</p> <p>For use in sea and brackish water (off-shore), as well as chemically aggressive water, max. water temperature up to 40°C/104°F, max. sand content of 25 mg/l and max. particle size of 2 mm.</p> <p>Please absolutely have the material resistance checked by the manufacturer by means of a water analysis.</p>			
1.1	<p>Hydraulic:</p> <p>Single- or multi-stage semi-axial / axial submersible pump in waterworks design for vertical installation in stage design.</p> <p>All casing parts in high-quality cast design.</p> <p>Shaft and connecting elements of high-alloyed stainless steel.</p> <p>Impellers in solid full metal design, with exchangeable wear rings of wear-resistant materials.</p> <p>Adjustment of the duty point possible by trimming of impeller.</p> <p>Shaft guided by metal or rubber slide bearings.</p> <p>Radial bearing completely lubricated by the pumped liquid and maintenance-free.</p> <p>The hydraulic is located in the lower part of the unit and equipped with an inlet strainer.</p>			
1.2	<p>Motor:</p> <p>"NEMA standard" submersible motor in wet type technology.</p> <p>In three-phase A.C. design with rewindable stator.</p> <p>Motor stator, shaft ends and connecting elements of stainless steel.</p> <p>Motor end parts in solid cast design.</p> <p>With integrated water cooling shroud of stainless steel.</p> <p>Radial bearing by water-lubricated and -cooled slide bearings of special artificial carbon, with spiral and longitudinal slots included.</p> <p>Mitchell-type bearing for high loads .</p> <p>Supporting plate and tilting segments of stainless steel, mobile wear ring of artificial carbon. With integrated counter supporting disc of artificial carbon for negative axial loads.</p> <p>Motor shaft sealing by 2 mechanical shaft seals completely of silicon-carbide, with intermediate separation chamber.</p> <p>Motor filling with pure drinking water or water/propylene glycol.</p> <p>Optional with winding temperature control by cold-type or PT100-thermistors and compensation tank to control the level of the motor filling.</p>			
1.3	<p>Non-return valve:</p> <p>Non-return valve directly built-on in heavy design, spring-mounted for vertical installation.</p> <p>Casing parts of high-quality cast materials, components completely of stainless steel / bronze (corrosion-free).</p>			
1.4	<p>Cable:</p> <p>Highly-resistant submersible cable "Hydrofirm T", with sheathing on EPR basis, with drinking water approval as per BAM ("Federal Institute for Test of Equipment").</p> <p>Max. limiting temperature of conductor: 90° C</p>			

Specification text - EMU Bottom intake pump - Material Design „A“

Item	Description	Unit price	Quantity	Total price
1	<p>Bottom intake pump</p> <p>suitable for pumping water in case of low water levels due to suction piece and pump end located below.</p> <p>Make:</p> <p>Pump type:</p> <p>No. of stages:</p> <p>Installation:</p> <p>Capacity: l/s</p> <p>Total man. head: bar</p> <p>Curve no.:</p> <p>Dimension sheet no.:</p> <p>Total efficiency (pump + motor): %</p> <p>Speed: r.p.m.</p> <p>Motor power: kW</p> <p>Operating voltage: V</p> <p>Starting:</p> <p>Discharge connection: DN/PN</p> <p>Outside diameter: mm</p> <p>Construction length: mm</p> <p>Weight: kg</p> <p>Material:</p> <ul style="list-style-type: none"> - impellers/diffusers: - pump casings: - motor casings: - shaft: - screwed connections: - motor sealing: <p>Motor filling:</p>			
2	<p>Cable:</p> <p>suitable for drinking water, connected at the motor ready for operation</p> <p>section: mm²</p>			